

Product details

Company profile

Transactions

Report Suspicious Activity!

Product Introduction Products Description Rack Optional Inverter Support Customized Services Packing and Shipping < >

Supply Ability 50000 Piece/Pieces per Month

Packaging & delivery

Packaging Details packaging.
Port Shenzhen
Picture Example:



Lead time?

Table with 3 columns: Quantity(pieces), 1 - 15, >15; Lead time (days), 20, To be negotiated

Online Customization

Click the image below to start online customization for the design you want.



Customise Now

All from 11% off

Limited Time Offers

2000:45:54

See all products



US \$108.58

US-\$122.00

MOQ: 4 Piece/Pieces 11% off



US \$541.80

US-\$602.00

MOQ: 1 Set/Sets 10% off

Applications:

- 1.Energy Storage -Solar-Wind Power System / City Grid (On/Off) / Community and Family
2.Back-up System and UPS -Telcom Base / CATV system / Computer Server Center / Medical Instrumnt / Military Equipment
3.Other Applications -Security and Electronics / Mobile POS, Mining Lihgt / Torch / LED Light / Emergency Light
-RV Motorhome /Golf Carts Battery / Boat Marine Yachts / Electric Skateboard / Electric bike / Electric Scooter / Electric bicycle
-LED Backup / Engine Starting Battery,etc

Messenger

Product details

Company profile

Transactions

Report Suspicious Activity!

Product Introduction Products Description Rack Optional Inverter Support Customized Services Packing and Shipping < >



Maximum 15 Parallel Connections

>6000 Cycles Reliable Performance

5 Years Technical Support

Smart BMS Communication Protocol

Plug in and Play

Supports Multiple Inverter Brands

Product Introduction

Related Products

48v 50AH 80AH 100ah 150AH 200...
US\$688.00 - US\$2,550.00 / piece
 1.0 piece

BR-48200B 48V 51.2V 200AH 9.6k...
US\$1,569.00 - US\$2,550.00 / piece
 1.0 piece

BW48230B 51.2V 230AH 11776wh...
US\$2,560.00 - US\$2,580.00 / piece
 1 piece

Products Description

Messenger

Product details

Company profile

Transactions

Report Suspicious Activity!

Product Introduction Products Description Rack Optional Inverter Support Customized Services Packing and Shipping < >

Series or Parallel Connection	16S1P	16S1P	16S1P
Maximum Charge Current	100A	200A	200A
Charge Current (-20 to - 10 °C)	≤0.05C	≤0.05C	≤0.05C
Recommended Charge Voltage	56V-57.6V	56V-57.6V	56V-57.6V
BMS Charge Voltage Cut-Off	57.6V (3.75±0.025vpc)	57.6V (3.75±0.025vpc)	57.6V (3.75±0.025vpc)
Reconnect Voltage	54.6V (3.34 ±0.05vpc)	54.6V (3.34 ±0.05vpc)	54.6V (3.34 ±0.05vpc)
Dimensions (L x W x H)	440*435*222mm (17.3x17.1x8.74")	480*248*618mm	475*255*770mm
Weight	70KG with wooden packing	:116KG with wooden packing	138KG with wooden packing
Communication Interface	RS485 (Optional)	RS485 (Optional)	RS485/CAN (Optional)
Case Material	Metal	Metal	Metal
Enclosure Protection	IP54	IP54	IP54
Maximum Continuous Discharge Current	100A	200A	200A
BMS Discharge Current Cut-Off	105A	230A	230A
Reconnect Voltage	45V	45V	45V
Discharge Temperature	-20 to 60°C (-4 to 140 °F)	-20 to 60°C (-4 to 140 °F)	-20 to 60°C (-4 to 140 °F)
Charge Temperature	0 to 45°C (32 to 113 °F)	0 to 45°C (32 to 113 °F)	0 to 45°C (32 to 113 °F)

St
MSt
4Re
Contact
supplierFl
30
Chat nowBrowsing
History

Messenger

